

CR 250V

Fall arrester for vertical work

EN 360

CR 250V is intended for work requiring considerable displacement in relation to the point of attachment. No need to use a safety shock absorber. No need to use AZ 800 cable when working horizontally.

SPECIAL FEATURES



Protection for maximum user's weight of 140 kg



Protection for 1 person



Device for vertical use

PARAMETERS

Material composite

Min. static strength 12 kN

ROPE

Diameter Ø 4 mm

Material galvanized steel

MECHANISM

Material galvanized steel

CARABINERS

Carabiner model AZ 002ASI

CR 250V

Fall arrester for vertical work

VARIANTS

| ref. no. | case colour | length [m] |
|----------|---------------------|------------|
| CR250V06 | bright yellow-green | 6 |
| CR250V10 | bright yellow-green | 10 |
| CR250V12 | bright yellow-green | 12 |
| CR250V15 | bright yellow-green | 15 |
| CR250V06 | black | 6 |
| CR250V10 | black | 10 |
| CR250V12 | black | 12 |
| CR250V15 | black | 15 |
| CR250V06 | blue | 6 |
| CR250V10 | blue | 10 |
| CR250V12 | blue | 12 |
| CR250V15 | blue | 15 |
| CR250V06 | grey | 6 |
| CR250V10 | grey | 10 |
| CR250V12 | grey | 12 |
| CR250V15 | grey | 15 |
| CR250V06 | red | 6 |
| CR250V10 | red | 10 |
| CR250V | red | 12 |
| CR250V15 | red | 15 |

CR 250V

Fall arrester for vertical work

PHOTOS 360 (ROTATING)

