

Product Description

Safety cabinets are constructed of sturdy 18-gauge(1-mm)thick double-wall,welded steel with 1-1/2'(38-mm)of insulating air space for fire resistance.

Galvanized steel shelves direct spills to back and bottom of a leakproof 50mm/150mm bottom sump.

Durable lead-free epoxy/polyester powder-coat finish provides excellent chemical resistance capacity.

Three-point stainless steel bullet latching system makes it work safely every time.Equipped with Adjustable legs and Grounding wires.



Model No. and Color Options	ZYC0030R/Red
Capacity	30 gallons/114Liter
No.of Doors	1
Door Type	Manual closing
No. of Shelves	1
Adjustable Shelves	Yes
Dimensions(Exterior)	1120H*1090W*460D(mm)
Dimensions(Interior)	1020W*910H*375D(mm)
Compliance	OSHA 29 CFR 1910.106 & NFPA

Detailed Images

* Designed to meet OSHA and NFPA 30 standards, flammable cabinet is constructed of sturdy 18-gauge (1-mm) thick double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space for fire resistance.

* High-performance, self-latching doors close easily and securely for maximum protection under fire conditions.

* Fail-safe closing mechanism ensures three-point stainless steel bullet latching system works every time.

* For added security, Solid-K™ handle comes with a cylinder lock and key set or accepts an optional padlock.

* Ref-L™ reflective warning labels are highly visible under fire conditions or during power outages when illuminated with a flashlight.

* Galvanized steel shelves direct spills to back and bottom of a leakproof sump. They adjust on 2.36-in (60-mm) centers for versatile storage. Cabinets also feature a leakproof 2-in (51-mm) bottom sump, dual vents with flame arresters, four adjustable self-leveling feet, grounding connector and trilingual warning label.

Durable lead-free epoxy/polyester powder-coat finish provides excellent chemical



