

Product Description

Safety cabinets are constructed of sturdy 18-gauge(1-mm)thick double-wall,welded steel with 1-1/2'(38-mm)of insulating air space for fire resistance.

Galvanized steel shelves direct spills to back and bottom of a leakproof 50mm/150mm bottom sump.

Durable lead-free epoxy/polyester powder-coat finish provides excellent chemical resistance capacity.

Detailed Images

* Designed to meet OSHA and NFPA 30 standards, flammable cabinet is constructed of sturdy 18-gauge (1-mm) thick double-wall,welded steel with 1-1/2-in (38-mm) of insulating air space for fire resistance.

* High-performance, self-latching doors close easily and securely for maximum protection under fire conditions.

* Fail-safe closing mechanism ensures three-point stainless steel bullet latching system works every time.

* For added security, Solid-K™ handle comes with a cylinder lock and key set or accepts an optional padlock.

* Ref-L™ reflective warning labels are highly visible under fire conditions or during power outages when illuminated with a flashlight.

* Galvanized steel shelves direct spills to back and bottom of a leakproof sump. They adjust on 2.36-in (60-mm) centers for versatile storage. Cabinets also feature a leakproof 2-in (51-mm) bottom sump, dual vents with flame arresters, four adjustable self-leveling feet, grounding connector and trilingual warning label.

* Durable lead-free epoxy/polyester powder-coat finish provides excellent chemical resistance.

Size Information

Name	Huanawell Model	Number of doors and style	Shelf	Capacity	Ext. Dimension H*W*D/MM
	ZYC0004	1 door, manual	1	4Gal/15L	560*430*430
	ZYC0012	1 door, manual	1	12Gal/45L	890*590*460
	ZYC0022	1 door, manual	2	22Gal/83L	1650*590*460
Flammable	ZYC0030	2 door, manual	1	30Gal/114L	1120*1090*460
Cabinet	ZYC0045	2 door, manual	2	45Gal/170L	1650*1090*460
	ZYC0060	2 door, manual	2	60Gal/227L	1650*860*860
	ZYC0090	2 door, manual	2	90Gal/340L	1650*1090*860
	ZYC0110	2 door, manual	2	110Gal/410L	1650*1500*860