

## Product Description

- \* Designed to meet OSHA and NFPA 30 standards, flammable cabinet is constructed of sturdy 18-gauge (1-mm) thick double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space for fire resistance.
- \* High-performance, self-latching doors close easily and securely for maximum protection under fire conditions.
- \* Fail-safe closing mechanism ensures three-point stainless steel bullet latching system works every time.
- \* For added security, Solid-K™ handle comes with a cylinder lock and key set or accepts an optional padlock.
- \* Ref-L™ reflective warning labels are highly visible under fire conditions or during power outages when illuminated with a flashlight.
- \* Galvanized steel shelves direct spills to back and bottom of a leakproof sump. They adjust on 2.36-in (60-mm) centers for versatile storage. Cabinets also feature a leakproof 2-in (51-mm) bottom sump, dual vents with flame arresters, four adjustable self-leveling feet, grounding connector and trilingual warning label.
- \* Durable lead-free epoxy/polyester powder-coat finish provides excellent chemical resistance.



## Size Information

Name	Huanawell Model	Number of doors and style	Shelf	Capacity	Ext. Dimension H*W*D/MM
	ZYC0004R	1 door, manual	1	4Gal/15L	560*430*430
	ZYC0012R	1 door, manual	1	12Gal/45L	890*590*460
	ZYC0022R	1 door, manual	2	22Gal/83L	1650*590*460
Combustible	ZYC0030R	2 door, manual	1	30Gal/114L	1120*1090*460
Cabinet	ZYC0045R	2 door, manual	2	45Gal/170L	1650*1090*460
	ZYC0060R	2 door, manual	2	60Gal/227L	1650*860*860
	ZYC0090R	2 door, manual	2	90Gal/340L	1650*1090*860
	ZYC0110R	2 door, manual	2	110Gal/410L	1650*1500*860